


Clarke®

DirectAir™ Electric Drying Systems



www.clarkeus.com

Clarke®
Quality Since 1916.



KEY FEATURES

- Unlimited applications
- Powerful 3 speed motor produces desired air flow for application requirements
- Multipositional 0°, 45°, 90° - aims air flow where it is needed most
- Easily transported to remote worksites
- Stacks easily for increased air flow
- Exceptional air movement for drying, exhausting or cooling

SPECIFICATIONS

Air Flow	3000/2000/1300 CFM
Motor	1/2 hp thermally protected
Fan (h x w)	10-5/8 x 10-1/2 in (27 x 26.6cm)
Power Cable (with grip)	35 ft (10.9 m)
Switch	4-position
Agencies	Pending
Operating Positions	0°, 45°, 90°
Additional	Stackable
Size (L x W x H)	18-1/2 x 17 x 16 in 47 x 43.1 x 40.6 cm
Weight	30 lb (13.6 kg)
Shipping Weight	35 lb (15.8 kg)

PRODUCT

- Aerodynamic design moves up to 3000 cubic feet of air per minute
- Versatile dryer for use on damp carpeting or wet tile floors
- Rugged one piece Roto-molded housing
- Super efficient “squirrel cage” type fan moves air quietly

EASE OF USE

- Stackable for storage - requires less space
- Multipositional 0°, 45°, 90°
- Balanced carrying handle

- Convenient cord wrap eliminates cord tangle
- Molded in cord grip locks the cord in the storage position
- Single control knob for easy operation

PRODUCTIVITY

- Moves more air for the faster drying of floors, carpets, walls
- Easily stacked for increased airflow
- Evacuates air quickly from rooms for improved air quality
- Easily serviced

- Inflates advertising balloons and inflatable playgrounds

SAFETY

- Quiet operation
- Vibration dampening feet
- Water resistant power cord
- Screen enclosed airflow movement - keeps foreign objects out of fan
- Thermally protected motor
- See your Clarke® distributor for a full line of floor care products

Clarke®

2100 Hwy. 265
Springdale, AR 72764
www.clarkeus.com

DISTRIBUTED BY:

Customer Relations: 1.800.253.0367
Fax Orders to: 1.800.825.2753
Technical Service: 1.800.356.7274