

EZ-8 Drum Sander



Because Pride Still Matters.

A Nilfisk-Advance Brand

Clarke[®]
American Sanders

EZ-8 Drum Sander



Key Features:

- Powerful performance in a small package
- Fully-enclosed dust free motor
- Available in standard clamp or expandable drum models
- Non-slip cogged belt
- Disassembles easily for transport or storage
- Rugged cast aluminum construction
- Lever-controlled drum

	EZ-8	
Part Number	07057A (Clamp Style)	07058A (Expandable Drum)
HP / Volts / Frequency	1.5 HP (1.12 kw) / 115 volt 60 Hz*	
Contact Drum Size	8 in. (20.32 cm)	
Sandpaper Size (clamp drum)	8 x 19.5 in. (20.3 x 49.5 cm)	
Expandable Drum Sandpaper Size	8 x 19 in. belt (20.3 x 48.2 cm)	
Drive	Non-slip cogged timing belts	
Bag Capacity	2 cu. ft. (56.6 l.)	
Drum Speed	1800 RPM	
Power Cable	40 ft. (12.2 m)	
Abrasive Speed	2680 SFM (Clamp Style) / 2830 SFM (Expandable Drum)	
Dust Fan/Speed Flow	4800 RPM / 76 CFM	
Leveling Control	Externally-adjusted	
Operating Control	Lever	
Motor Starter	Mechanical relay	
Wheels (cushion rubber)	3 in. (7.62 cm) diameter	
Dimensions (L x W x H)	39.25 x 15.5 x 32 in. (99.7 x 39.37 x 81.28 cm)	
Weight	105 lbs. (47.63 kg)	
Shipping Weight	120 lbs. (54.43kg)	
Warranty	1 Year Parts & Labor	

*Also available in 110V or 230V 50Hz

WHAT THE EZ-8 DOES BEST:

- Powerful performance
- Easy-to-use operation
- Comfort for operator
- Innovative lever-controlled drum
- Easy to transport and store

SAFETY FEATURES:

- Dust free motor
- Dust bag captures airborne dust

OPTIONAL ACCESSORIES:

- Extra sandpaper
- Dust bags
- Wheel assemblies



We believe in our products and our people. That's why we created the PRIDE PROGRAM:

- A 60-day satisfaction guarantee on our machines
- A chance for customers to win a free edger by returning the product's registration card
- Direct communication with our factory through our new Quality Management System

Clarke® American Sanders

2100 Hwy. 265
Springdale, AR 72764
www.americansanders.com

DISTRIBUTED BY:

Customer Relations: 1.800.545.3454
Fax Orders to: 1.800.825.2753
Technical Service: 1.800.356.7274