

Clarke®

3DS Electric Fine Finish
Orbital Sander



www.americansanders.com


Clarke®
American Sanders

Because Pride Still Matters

3DS

Electric Fine Finish Orbital Sander

Clarke® American Sanders



KEY FEATURES:

- Powerful totally enclosed motor requires less maintenance
- Large non-marking transport wheels
- Heavy cast aluminum housing
- High speed sanding disk
- Produces a flatter floor
- Controls sanding dust
- Removes scratches produced by drum or belt sanding process
- Ideal for parquet or herringbone patterns



Specifications

	230V 60 Hz	230V 50 Hz	230V 50 Hz
Part Number	07082C	07112A	07085C
Sanding Path	18.75 in. (47.63 cm)		
Sanding Path Diameter	8 in.		
Motor	Fully-Enclosed 3 HP (2.2 kW) single phase, fan-cooled		
Power Cable	40 ft. (12 m)	40 ft. (12 m) with BS - 1363 Plug	40 ft. (12 m) with IEC - 309 Plug
Power Requirements	208-230V 15A 60 Hz	220-240 13A 50 Hz	220-240 15A 50 Hz
Speed of Sanding Path	717 RPM (loaded)		
Vacuum Motor	1200W	800W	1200W
Sanding Unit Weight	109 lbs. (50 Kg)		
Chassis Weight	37 lbs. (17 Kg)		
Size (L x W x H)	35 x 20 x 39.5 in. (89 x 51 x 100 cm)		
Total Weight (w/out vacuum)	146 lbs (67 Kg)		
Total Weight (w/ vacuum)	163 lbs. (74 Kg)		
Shipping Weight	234 lbs. (106 Kg)		
Warranty	One Year Parts & Labor		

Check out these other great orbital sanders!



OBS 18 & OBS 18DC

EZ-Sand



DISTRIBUTED BY:

Clarke®

2100 Hwy. 265
Springdale, AR 72764

www.americansanders.com

Customer Service: 1.800.253.0367

Fax Orders to: 1.800.825.2753

Technical Service: 1.800.356.7274

©2005 ALTO U.S. Inc., All Rights Reserved. Specifications subject to change without notice. P/N 79943A Rev. 07/07

Pride
PROGRAM

**We believe in our products and our people.
That's why we created the PRIDE PROGRAM:**

- A 60-day satisfaction guarantee on our machines
- A chance to win a free edger by returning the product's registration card
- Communication with us through our Quality Management System



ISO 9001
FILE #A2907
CLARKE TECHNOLOGY