



TimberGuard™ SELECT

Water-Based Wood Floor Coating



TimberGuard Select is a single component, water-based urethane/acrylic wood floor finish that is ideal for residential and light commercial settings. **TimberGuard Select** is a highly durable finish with excellent flow characteristics, and inhibits the growth of stain and odor causing bacteria 24/7.

- Colorless to ensure the natural wood or stain color appears as intended.
- Low VOC formula.
- Urethane/acrylic formulation provides easy-to-apply durability.
- Quick dry time – normally 2-3 hours.
- Water soluble which allows for easy clean-up.
- Can be applied with a T-bar, Microfiber Roller (1/4 inch nap), or Cut-in Pad.

INDUSTRY-LEADING DURABILITY!

Taber Abrasion Durability Results



Taber Abrasion testing performed by third party independent laboratory.

SURFACES



WOOD FLOORS

TECHNICAL DATA

Description Water-based polyurethane-acrylic finish

Appearance Milky white liquid

Available Sheens Super Matte, Satin, Semi-Gloss

Hardener Oxygen and proprietary self-crosslinking

pH 7.8
ASTM E70-07

Specular Gloss (60°) Super Matte: 5-10
ASTM D1455-87 (2008) Satin: 20-25
Semi-Gloss: 45-50

Viscosity (Brookfield) 140 centipoise

Coverage Rate 500-600 ft²/gal

Dry Time 2-3 hours for first coat

VOC <275 g/L
40 CFR Part 59 Subpart D

Non-volatile solids 32%
ASTM D2834-95 (2008)

Fragrance Characteristic

Slip Resistance UL Certification Pending
ULTM410

Shelf Life 1 year
ASTM D1791-93 (2008)

Density 8.7 lb/gal
ASTM D1475-13 (2008)

Detergent Resistance Excellent
ASTM D3207-92 (2008)

Freeze/Thaw Passes 3 cycles
ASTM D3209-93 (2008)

Container 1 gal (3,8 liters), wide mouth (63mm) bottle

