



TimberGuard™ VARSITY

Water-Based Urethane Wood Floor Coating



TimberGuard Varsity is a one component, water-based urethane wood floor coating specially formulated for sports floors. Varsity goes down smooth and dries quickly, making it ideal for annual recoats. MFMA Compliant.

- Colorless to ensure the natural wood or stain color appears as intended.
- Low VOC formula.
- High gloss sheen exceeds 85 at 60° specular gloss.
- Quick dry time – normally 2-3 hours.
- Water soluble which allows for easy clean-up.
- Can be applied with a T-bar, Roller (1/4 inch nap), or Cut-in Pad.



SURFACES



WOOD FLOORS

TECHNICAL DATA

Description	Water-based polyurethane coating
Appearance	Milky white liquid
Available Sheens	High Gloss
pH <small>ASTM E70-07</small>	7.6
Specular Gloss (60°) <small>ASTM D1455-87 (2008)</small>	High Gloss: >85
Viscosity (Brookfield)	<60 centipoise
Coverage Rate	500-600 ft ² /gal
Dry Time	2-3 hours for first coat
VOC <small>40 CFR Part 59 Subpart D</small>	<250 g/L
Non-volatile solids <small>ASTM D2834-95 (2008)</small>	30%
Fragrance	Characteristic
Slip Resistance <small>ULTM410</small>	UL Certification Pending
Shelf Life <small>ASTM D1791-93 (2008)</small>	1 year
Density <small>ASTM D1475-13 (2008)</small>	8.5 lb/gal
Detergent Resistance <small>ASTM D3207-92 (2008)</small>	Excellent
Freeze/Thaw <small>ASTM D3209-93 (2008)</small>	Passes 3 cycles
Container	719HGPL5: 5 gal (19 liters) pail 719HGFS: 2 x 2.5 gal (9.5 liters) bottle

