



218-OS ORBITAL SANDER

PRODUCT DESCRIPTION

The random-orbital sanding action of the DEWALT 218-OS Orbital Sander removes the scratch patterns left by drum or rotary sanders, leaving a smooth, flat floor ready for refinishing. At 3,600 orbits per minute, the DEWALT 218-OS Orbital Sander sands faster than any other orbital sander available. With torque-less operation for enhanced operator comfort, the DEWALT 218-OS Orbital Sander is perfect for interim “screen and recoat” and fine finish sanding jobs.

1. The totally enclosed, fan cooled motor, eliminates overheating and the need for motor cleaning.
2. Heavy duty cast aluminum main frame and pad driver plate for added strength.
3. Durable independent dust pickup fan for effective dust containment.
4. Dust pipe allows for easy attachment of 1-1/2 or 2 inch vacuum hoses for improved dust containment.
5. Molded dust skirt included for improved dust containment.
6. Transparent molded plug has an internal light that serves as a power indicator.

PRODUCT INFORMATION

Model# DXAS07081B



TECHNICAL DATA

Electrical Motor	1.0 hp Universal, totally enclosed, 115V, 60 Hz
Sanding Path	18 in (45.7 cm)
Power Cord	50 ft (15.3 m) gray, non-marking rubber
Sanding Pad Size	12 in x 18 in
Abrasive Speed	3,600 orbits per minute
Sound Level	74 dBA
Wheels	(2) 3 in
Size (L x W x H)	18 in x 20 in x 45 in (46 cm x 51 cm x 114 cm)
Machine Weight	125 lbs (56.7 kg)
Shipping Weight	145 lbs (66 kg)
Warranty	Machine: Parts & Labor - 2 years*

*Excludes consumable wear items

Specifications are subject to change without notice.

DEWALT 218-OS Rotary Sanders are offered exclusively by American Sanders. 800-334-2248

rev: 02/26